

PRODUCT DATA SHEET

No. 10535

APRIL 2005

RONSEAL ONE COAT MATT BLACK PAINT

Ronseal One Coat Black Matt Paint is a highly opaque, quick drying, exterior Paint, which offers a tough and durable quality matt finish. Ronseal One Coat Black Matt Paint provides long lasting colour and protection from all weather types.

INTRODUCTION

Ronseal One Coat Black Matt Paint provides a highly opaque, non reflective finish black matt finish for the long term protection of exterior wood work including oak beams, soffits and fascias. Ronseal One Coat Black Matt Paint can also be used on plastic pipework and guttering.

Ronseal One Coat Black Matt Paint has a unique formulation based on a novel, water based polymer, which resists cracking, blistering and peeling throughout it's extended life span. contains high quality, iron oxide pigments, to provide optimum protection against visible and ultraviolet light degradation and discolouration, as well as providing an attractive matt finish.

Ronseal One Coat Black Matt Paint requires no additional primers or basecoats. It is a fast drying formulation, which allows rapid completion of any exterior project. The optimum viscosity formula gives easy application and maximum film build.

Ronseal One Coat Black Matt Paint is showerproof in one hour and recoatable in 4 hours (as required in areas of high porosity or bare substrate)

Ronseal One Coat Black Matt Paint transforms the substrate providing a smooth, black matt finish.

COMPOSITION

Ronseal One Coat Black Matt Paint is based on a superior quality, highly flexible and durable, acrylic polymer system. It contains high quality, carbon black pigments to colour and protect the substrate and resist fading. Ronseal One Coat Black Matt Paint contains water repellent additives to enhance it's protective qualities.

PROPERTIES

Viscosity – Viscous liquid with a slightly structured appearance.

VOC Content – Low (0.3-7.99% w/v).

Odour – Low.

Water Repellence – Good.

Miscible with water.

Colour/finish- Black Matt

FIELDS OF APPLICATION

Ronseal One Coat Black Matt Paint is recommended for the treatment of all exterior woodwork, work including oak beams, soffits

and fascias. Ronseal One Coat Black Matt Paint can also be used on plastic pipework and guttering.

PREPARATION

Ronseal One Coat Black Matt Paint should only be applied to clean, dry surfaces that are free from oil, grease and other contamination. All previous loose or flaking material must be removed before application. As Ronseal One Coat Black Matt Paint provides an opaque finish any marks, blemishes or stains in the substrate will not show after treatment.

Remove mould, algae, lichens and moss with a stiff brush and scraper. Eradicate residual growth using a proprietary fungicidal cleaner preferably applied in dry weather. Leave for 48 hours, rinse thoroughly with water and allow to dry before application.

Ronseal One Coat Black Matt Paint can be applied to surfaces which have previously been treated with exterior paints, providing these are in a sound condition. Loose or flaking coatings should be scraped back to a sound surface.

APPLICATION

Stir Ronseal One Coat Black Matt Paint well before and during use. Apply an even but not excessive coat. Ensure that all surfaces requiring protection are covered. If a second coat is required allow 4 hours before overcoating.

For best results use a synthetic filament brush to apply a full even coat. Always finish all surfaces in the same direction. Do not apply in direct sunlight.

COVERAGE

10m² per litre, depending on type, texture and absorbency of the substrate.

DRYING TIME

Ronseal One Coat Brick and Tile Paint is touch dry and showerproof in 1 hour. Drying time varies with temperature, relative humidity and absorbency of substrate. Allow 4 hours before recoating if required.

CLEANING OF TOOLS

All equipment should be cleaned immediately after use with water and detergent.

Remove as much product as possible from tools and equipment before washing.

Wipe the tin and lid rim with a clean cloth prior to resealing the tin.

MAINTENANCE

Clean away dirt, dust and grease from the surface, and allow to dry. Remove any loose and flaking material. Apply 1 to 2 coats of Ronseal One Coat Black Matt Paint as required.

COLOUR VARIANTS

Ronseal One Coat Black Matt Paint is available in a Black Opaque Matt finish.

IMPORTANT NOTES

This product contains no added lead. However, wooden and metal surfaces particularly in pre-1960 buildings may have previously been treated with paint containing lead pigments. Special care must be taken when sanding or stripping. Professional decorators should carry out a COSHH assessment before any work is carried out. For further information consult our Technical Services Department.

Always pre-test the product on a small inconspicuous area to confirm colour suitability prior to the treatment of the whole area.

Do not Ronseal One Coat Black Matt Paint if the moisture content of the wood exceeds 20%.

Clean splashes off glass whilst wet.

Do not apply in direct sunlight.

Do not apply below 10°C or in conditions of high humidity.

Conventional paints should be allowed to age for at least one month before the application of Ronseal One Coat Brick and Tile Paint.

STORAGE

Store in a cool, dry, well ventilated place away from heat and sources of ignition. Store upright and carefully reseal partly used containers.

The shelf life of Ronseal One Coat Black Matt Paint in airtight containers is at least 3 years.

HEALTH AND SAFETY

Observe and follow all warnings and instructions for use shown on the pack.

Avoid contact with skin and eyes.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After contact with skin, wash immediately with plenty of water.

Ensure maximum ventilation during application and drying.

Specific health and safety data sheets are available on request.

FLAMMABILITY

Flash point above 61°C.
Non-flammable product.

SUPPLY

Obtainable from DIY retailers, paint suppliers and builders merchants.

SIZES

750ml litre resealable containers.

DISPOSAL

Some local authorities have special facilities for disposal of waste paints/varnishes.

Do not empty product into drains or watercourses.

LIABILITY

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assume responsibility for any work as the ultimate result depends on factors beyond our direct control. Standard codes of painting practice should be followed.

INFORMATION AND SERVICE

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

DATA SHEETS

Data sheets on other Ronseal products are available on request from our Technical Services Department.

Ronseal Ltd. has been registered to BS EN ISO 9000 1994 (Registered Firm No. FM 1669/1).

Ronseal Ltd. operate an Environmental Management System that complies with the requirements of BS 7750:1994, Certificate No. EMS 35924.

Ronseal Ltd. has achieved Investors in People certification (certificate number 59586).

©RONSEAL LTD.,

**Thornccliffe Park
Chapelton
Sheffield
S35 2YP**

Tel: (0114) 246 7171

Fax: (0114) 245 5629

E. Mail: enquiry@ronseal.co.uk

Website: www.ronseal.co.uk

Ronseal is a Registered Trademark of the Sherwin Williams Company.

APRIL, 2005
ISSUE 1