

PRODUCT DATA SHEET

No. 10545

APRIL 2005

RONSEAL ONE COAT SATIN BLACK PAINT

Ronseal One Coat Satin Black Paint is superior, quick drying paint, which offers an exceptional quality mid-sheen finish for interior metal. Ronseal One Coat Satin Black Paint is an easy one coat application which provides a fresh and rejuvenated appearance.

INTRODUCTION

Ronseal One Coat Satin Black Paint is a decorative product for interior metal, it can also be used on wood, furniture and wrought iron.

Ronseal One Coat Satin Black Paint has a unique formulation based on a self cross-linking, water based polymer, combined with flash rust inhibitors. Ronseal One Coat Satin Black Paint contains high quality pigments, which provide excellent covering power. The product dries to a soft satin finish.

Ronseal One Coat Satin Black Paint requires no additional primers or basecoats. It is a fast drying formulation, which allows rapid completion of any interior project. The optimum viscosity formula gives easy application and maximum film build.

Ronseal One Coat Satin Black Paint dries in one hour and is recoatable in 4 hours (as required in areas of high porosity)

Ronseal One Coat Satin Black Paint transforms the substrate providing a smooth, satin, opaque black finish.

COMPOSITION

Ronseal One Satin Black Paint is based on a superior quality, flexible and durable, self cross-linking acrylic polymer system. It contains high quality, carbon pigments to colour and protect the substrate and resist fading. Ronseal One Satin Black Paint contains flash rust inhibiting additives to allow the product to be applied directly to bare metal.

PROPERTIES

Viscosity – Viscous liquid with a slightly structured appearance.
VOC Content – Low (0.3-7.99% w/v).
Odour – Low.
Water Repellence – Good.
Miscible with water.

FIELDS OF APPLICATION

Ronseal One Coat Satin Black Paint is recommended for application to interior metal and wood for example furniture and wrought iron. It is not suitable for use on ceramics.

PREPARATION

Ronseal One Coat Satin Black Paint should only be applied to clean, dry surfaces that are

free from oil, grease and other contamination. All previous loose or flaking material must be removed before application. As Ronseal One Coat Satin Black Paint provides an opaque finish any marks, blemishes or stains in the substrate will not show after treatment.

Ronseal One Coat Satin Black Paint can be applied to surfaces which have previously been treated with interior paints, providing these are in a sound condition. Loose or flaking coatings should be scraped back to a sound surface.

When applying to bare wood the surface must be sanded with a medium grade sand paper, it must then be wiped with a clean cloth dampened with white spirit.

APPLICATION

Stir Ronseal One Coat Satin Black Paint well before and during use. Apply an even but not excessive coat. Ensure that all surfaces are sufficiently covered. If a second coat is required allow 4 hours before overcoating.

For best results use a synthetic filament brush to apply a full even coat. Always finish all surfaces in the same direction. Do not apply in direct sunlight.

COVERAGE

10m² per litre, depending on type, texture and absorbency of the substrate.

DRYING TIME

Ronseal One Coat Satin Black Paint is touch dry and showerproof in 1 hour. Drying time varies with temperature, relative humidity and absorbency of substrate. Allow 4 hours before recoating if required.

CLEANING OF TOOLS

All equipment should be cleaned immediately after use with water and detergent.

Remove as much product as possible from tools and equipment before washing.

Wipe the tin and lid rim with a clean cloth prior to resealing the tin.

MAINTENANCE

Clean away dirt, dust and grease from the surface, and allow to dry. Remove any loose and flaking material. Apply 1 to 2 coats of

Ronseal One Coat Satin Black Paint as required.

COLOUR VARIANTS

Ronseal One Coat Satin Black Paint is available in a black opaque satin finish.

IMPORTANT NOTES

This product contains no added lead. However, wooden and metal surfaces particularly in pre-1960 buildings may have previously been treated with paint containing lead pigments. Special care must be taken when sanding or stripping. Professional decorators should carry out a COSHH assessment before any work is carried out. For further information consult our Technical Services Department.

Always pre-test the product, on a small inconspicuous area to confirm colour suitability prior to the treatment of the whole area.

Do not use Ronseal One Coat Satin Black Paint if the moisture content of the wood exceeds 20%.

Dispose of sanding dust safely and store outside.

Do not use Ronseal One Coat Satin Black Paint on plastic type materials.

Clean splashes off glass whilst wet.

Do not apply in direct sunlight.

Do not apply below 10°C or in conditions of high humidity.

Conventional paints should be allowed to age for at least one month before the application of Ronseal One Coat Satin Black Paint.

STORAGE

Store in a cool, dry, well ventilated place away from heat and sources of ignition. Store upright and carefully reseal partly used containers.

The shelf life of Ronseal One Coat Satin Black Paint in airtight containers is at least 3 years.

HEALTH AND SAFETY

Observe and follow all warnings and instructions for use shown on the pack.

Avoid contact with skin and eyes.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After contact with skin, wash immediately with plenty of water.

Ensure maximum ventilation during application and drying.

When applying to large interior surface or in confined spaces, wear a face mask which is designed to prevent inhalation of solvent vapours.

Specific health and safety data sheets are available on request.

FLAMMABILITY

Flash point above 61°C.
Non-flammable product.

SUPPLY

Obtainable from DIY retailers, paint suppliers and builders merchants.

SIZES

250ml resealable containers.

DISPOSAL

Some local authorities have special facilities for disposal of waste paints/varnishes.

Do not empty product into drains or watercourses.

LIABILITY

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assume responsibility for any work as the ultimate result depends on factors beyond our direct control. Standard codes of painting practice should be followed.

INFORMATION AND SERVICE

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

DATA SHEETS

Data sheets on other Ronseal products are available on request from our Technical Services Department.

Ronseal Ltd. has been registered to BS EN ISO 9000 1994 (Registered Firm No. FM 1669/1).

Ronseal Ltd. operate an Environmental Management System that complies with the requirements of BS 7750:1994, Certificate No. EMS 35924.

Ronseal Ltd. has achieved Investors in People certification (certificate number 59586).

©RONSEAL LTD.,

**Thornccliffe Park
Chapelton
Sheffield
S35 2YP**

Tel: (0114) 246 7171

Fax: (0114) 245 5629

E. Mail: enquiry@ronseal.co.uk

Website: www.ronseal.co.uk

Ronseal is a Registered Trademark of the Sherwin Williams Company.

APRIL, 2005
ISSUE 1